

PRODUCT SPECIFICATION



screening and processing technology

Fleximat Ges.m.b.H.
Arndorf 68
8181 St. Ruprecht/Raab, Austria
T: +43 (0) 3178-289 85-0
F: +43 (0) 3178-289 85-44
M: +43 (0) 664-354 5400
E: office@fleximat.at
www.fleximat.at

Fleximat DELUXE

Chemical basic	Polyester cold cast system
Characteristics	Highly wear resistant cast polyurethane system
Area of application	Highly wear resistant coatings and moldings
Benefits	Extremely low wear Excellent mechanical properties High shear resistance
Resistance	Mainly for applications involving mechanically abrasive conditions
Operation temperature	Continuous use up to approx. 60 °C (dry) Short term use up to approx. 80 °C
Supplied Shore hardness	From 50 to 90 °Shore A
Shore hardness Screen Mats	FD 80 +/- 5 °Shore A
Color	Lime green

FLEXIMAT DELUXE M-plus

TECHNICALLY FLEXIMAT DELUXE - microbe resistant

certificated austrian quality products

Firmensitz: St. Ruprecht/Raab
Firmenbuch-Nr 376154 v
Handelsgericht Graz
UID ATU67195199
EORI-Nr.: ATEOS1000042793

bank details:
VOLKSBANK Steiermark AG
account no.: 309 8886 0001
bank code: 42320
IBAN: AT294232030988860001
BIC (swift-code): VBOEATWWGRA